

PRODUCT DATA SHEET

PLIOFLEX[®] MAGNIC

CHEMICAL DESCRIPTION

PLIOFLEX[®] MAGNIC is an oil-extended, emulsion polymerized styrene-butadiene copolymer with a non-staining antioxidant. It contains a mixed acid emulsifier and is salt-acid coagulated.

APPLICATIONS

PLIOFLEX[®] MAGNIC is typically used in color sensitive applications.

Application areas have included:

- Industrial Goods
- Hoses
- Belting
- Other Extruded Goods

TYPICAL PROPERTIES

PLIOFLEX [®] MAGNIC	
Color	light tan
Bound Styrene ¹ , %	23.5
Viscosity ¹ ML1+4 @ 100°C	41*
Oil Level, phr	37.5
Oil, type	Heavy Napthenic
Specific Gravity	0.94
Stabilizer	non staining

* Unmassed ML/4 – COA will also include calculated massed ML/4

PACKAGING

Cardboard Container

- Three cell cardboard boxes contain 24 - 80 lb film wrapped bales.
 - Dimensions: 50" L x 31.5" W x 55" H
 - Weight: Gross: 2044 lb, Net: 1920 lb

Returnable Container

- In select areas, returnable containers may be available.
- Returnable containers are collapsible aluminum containers that contain 36 – 80 lb film wrapped bales.
- Contact your sales representative for details.
- Other packaging types may be available for specific volumes and destinations.

Goodyear International Corporation

1452 East Archwood Avenue
Akron, Ohio, 44306-3296 - USA
1-877-579-4594

WARRANTY: Unless sold without warranty, this product is warranted to conform to Goodyear's applicable specifications in effect at the date of shipment. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. NO OTHER WARRANTY OF ANY KIND WHATSOEVER, EITHER ORAL OR WRITTEN, INCLUDING IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OTHER WARRANTY OF QUALITY IS EITHER EXPRESSED OR IMPLIED FOR THIS PRODUCT. GOODYEAR SHALL NOT BE LIABLE FOR SPECIAL, INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES, EVEN IF GOODYEAR HAS BEEN NOTIFIED OF THE POTENTIAL OF SUCH A LOSS OR CLAIM OR FOR ANY AMOUNT IN EXCESS OF THE APPLICABLE PURCHASE PRICE. This warranty is null and void should the product be subject to abuse, modification, misused or mishandled.

©Trademark, The Goodyear Tire & Rubber Company